CSD560

Slimline networking cable - CAT6A RJ45 - RJ45 U/UTP

Highlights:

- Ultra slim Ø 3.2 mm diameter
- PoE tested and approved (IEEE 802.3 af)
- LSHF jacket
- Tested up to 500 Mhz
- Thin, flexible and smooth cable jacket
- Time and space saving in rack applications
- Better airflow due to slim design
- Snagless & compact connector
- Multicoloured cables

Product information:

The CSD560 series is a series of Ultra-slim CAT6A U/UTP cables, which come available in a wide variety of lengths and colours. They offer reliable interconnections in various applications, ranging from general-purpose office computer systems to digital AV network systems. The ultra-slim construction with an outer diameter of only Ø 3.2 mm offers an elegant solution for office patch usage while guaranteeing the best possible space saving and airflow in rack applications. The compact and snagless connector design and numerous variants and colours offer reliable connections and a clear overview when wiring racks for various applications or protocols.

We reserve the right to change specifications without notice, this is part of our policy to continually improve our products.

Properties:

Product Features:

Application	AV & IT
Series	Connect Series

Physical Characteristics:

Outer jacket	Material	LSHF 3.2 mm (Ø)
	Colours	Black
		Green
		White
		Blue
		Red
		Yellow
Type of cable		U/UTP CAT6A Networking cable
Connection type		RJ45 male to RJ45 male

We reserve the right to change specifications without notice, this is part of our policy to continually improve our products.

Variants:

- CSD560B/0.15 - Black version - 0.15 meter
- CSD560B/0.3 - Black version - 0.3 meter
- CSD560B/0.5 - Black version - 0.5 meter
- CSD560B/1 - Black version - 1 meter
- CSD560B/1.5 - Black version - 1.5 meter
- CSD560B/2 - Black version - 2 meter
- CSD560B/3 - Black version - 3 meter
- CSD560B/5 - Black version - 5 meter
- CSD560BU/0.15 - Blue version - 0.15 meter
- CSD560BU/0.3 - Blue version - 0.3 meter
- CSD560BU/0.5 - Blue version - 0.5 meter
- CSD560BU/1 - Blue version - 1 meter
- CSD560BU/1.5 - Blue version - 1.5 meter
- CSD560BU/2 - Blue version - 2 meter
- CSD560G/0.15 - Green version - 0.15 meter
- CSD560G/0.3 - Green version - 0.3 meter
- CSD560G/0.5 - Green version - 0.5 meter
- CSD560G/1 - Green version - 1 meter
- CSD560G/1.5 - Green version - 1.5 meter
- CSD560G/2 - Green version - 2 meter
- CSD560R/0.15 - Red version - 0.15 meter
- CSD560R/0.3 - Red version - 0.3 meter
- CSD560R/0.5 - Red version - 0.5 meter
- CSD560R/1 - Red version - 1 meter
- CSD560R/1.5 - Red version - 1.5 meter
- CSD560R/2 - Red version - 2 meter
- CSD560W/0.15 - White version - 0.15 meter
- CSD560W/0.3 - White version - 0.3 meter
- CSD560W/0.5 - White version - 0.5 meter
- CSD560W/1 - White version - 1 meter
- CSD560W/1.5 - White version - 1.5 meter
- CSD560W/2 - White version - 2 meter
- CSD560Y/0.15 - Yellow version - 0.15 meter
- CSD560Y/0.3 - Yellow version - 0.3 meter
- CSD560Y/0.5 - Yellow version - 0.5 meter
- CSD560Y/1 - Yellow version - 1 meter
- CSD560Y/1.5 - Yellow version - 1.5 meter
- CSD560Y/2 - Yellow version - 2 meter

We reserve the right to change specifications without notice, this is part of our policy to continually improve our products.